



DVR-ES-P403
DVR-ES-P803
DVR-ES-P1604

P-series EOS DVR SPECIFICATIONS			
	P403H	P803H	P1604H
Video Input	4	8	16
Video Output	1 Monitor, 1 S-Video		
Loop Out	4	8	16
Live Displays	1, 4, PIP	1, 4, 6,8	1, 4, 6, 8, 9, 13, 16
Playback Displays	1, 4	1, 4, 6,8	1, 4, 6, 8, 9, 13, 16
Compression	WAVELET		
Live Display Resolution	NTSC 720*480, PAL 720*576		
Record & Playback Resolution	NTSC 720*243, PAL 720*288		
Alarm In/Out	4/1	8/1	16/1
Operating System	EMBEDDED LINUX		
System Control	Key buttons & Jog/Shuttle, IR Remote, Remote Client		
Live Display Speed (fps)			
NTSC	120	240	480
PAL	100	200	400
Max. Recording Speed (fps)	NTSC 60, PAL 50		
Audio Record	1ch (1ch Line In/Out, MIC Input)		

FEATURES

Display: Brightness, Contrast, Color Adjustments Per Channel
 Camera Title: 8 Characters per Channel
 Recording Mode: Manual, Schedule, Alarm, Motion
 Recording Method: 8 Levels of Compression Rate / Record Frame Rate Adjustment
 Recording Adjustments: Pre-Alarm: 140 frames / Post-Alarm: 20 sec. ~ 240 sec.
 Motion Detection Per Channel: 16 Grids / 15 Sensitivity Levels
 Search Mode: Date & Time, Camera , Alarm / Motion
 Playback Modes: Forward & Reverse: Pause, Frame by Frame, 2X, 4X, 8X, 16X
 Multi-tasking / Full Triplex: Simultaneous Live Display, Record, Playback, Back-up,
 Remote Transmission: Alarm Notification Automatic E-mail: Alarm, Video Loss, Power Loss, HDD Failure
 Watchdog: Power Failure Recovery : Auto Reboot w/ Maintaining Previous Record Settings
 System Utility: 2 Level Password /Auto Lock /Disk Format /Disk Check/ Fan Lock Detection
 Back Up: Ethernet, Remote PC, External Recording Devices, VCR
 External Recording Devices: Desk Raid, HDD, DAT, CD-RW, DVD-RW(- type), Flash Memory Stick
 Mini-Player for CD& DVD: Auto install when backing up files into CD or DVD
 Interface: USB2.0, RS-232, Ethernet
 HDD: UPTO 2 INTERNAL HDDs- Max 600GB
 Network: LAN, WAN, Internet, PSTN Line
 Remote Client Software: Plug-In For Internet Explorer 6.0 or Multi-Site Client Software(*)
 IR Remote Control Upto 99 DVRs

GENERAL

Power: 100 or 230VAC Switchable(50/60Hz)
 Power Consumption: 40.5W (220V), 39.5W(110V)
 Operation Temperature: 0-40 degrees C.
 Dimension / Weight: 360(W) x 340(D) x 100(H) / 6 Kg